





## ADVANTAGES

- OUTSTANDING THERMAL AND OXIDATION STABILITY
- ACTIVE CLEANING AGENTS
- LOW VOLATILITY
- PRECISELY BALANCED ADDITIVE COMPONENT SYSTEM







FORMULATED TO MEET

## **INDUSTRY STANDARDS**

LAUNCHER DEXRON III/ MERCON ATF IS A PREMIUM QUALITY AUTOMATIC TRANSMISSION FLUID RECOMMENDED FOR PRE 2006 GM AND FORD VEHICLES AS WELL AS HYDRAULIC AND POWER STEERING SYSTEMS. NOT RECOMMENDED WHEN FORD TYPE F OR FORD MERCON V/LV/SP TRANSMISSION FLUID IS REQUIRED.

CODE	GRADE	PACKING	MATERIAL
LMODEX3-121-P	DEXRON III/ MERCON	12x1L	PLASTIC
LMODEX3-45-P	DEXRON III/ MERCON	4x5L	PLASTIC

TYPICAL CHARACTERISTICS	METHOD	UNIT	DEXRON III ATF
ASTM Colour	ASTM D1500	-	Red
Brookfield Viscosity @ -40°C	ASTM D2983	mPa.s	10040
Density @ 15.6°C	ASTM D4052	g/ml	0.846
Flash Point, Cleveland Open Cup	ASTM D92	°C	220
Kinematic Viscosity @ 100°C	ASTM D445	mm²/s	7.4
Kinematic Viscosity @ 40°C	ASTM D445	mm²/s	36.3
Pour Point	ASTM D97	°C	-51
Viscosity Index	ASTM D2270	None	176

