




LAUNCHER

motor oil



CVT

TRANSMISSION FLUID



ADVANTAGES

- OUTSTANDING THERMAL AND OXIDATION STABILITY
- ACTIVE CLEANING AGENTS
- LOW VOLATILITY
- PRECISELY BALANCED ADDITIVE COMPONENT SYSTEM

LAUNCH its performance>>





LAUNCHER

motor oil

FORMULATED TO MEET
INDUSTRY STANDARDS

LAUNCHER CVT IS A PREMIUM QUALITY TRANSMISSION FLUID FOR MOST BELT AND CHAIN-DRIVEN CONTINUOUSLY VARIABLE TRANSMISSIONS

- EXCELLENT ANTI-WEAR PERFORMANCE
- DESIGNED TO PROVIDE EXCELLENT TORQUE TRANSFER
- EXCELLENT ANTI-SHUDDER DURABILITY



RECOMMENDED FOR USE IN:

- AUDI/VW (TL 52180; G 052 180)
- FORD (CVT30/CVT23/MERCON C)
- SUBARU (LINEARTRONIC CVTF)
- HONDA (HCF-2)
- NISSAN (NS-2)
- MITSUBISHI (CVTF-J1)
- BMW MINI COOPER (EZL 799)
- HYUNDAI/KIA (SP-CVT 1)
- SUZUKI (TC/NS-2/CVT GREEN 1)
- DODGE/JEEP (NS-2/CVT GREEN 1)
- DODGE/JEEP (NS-2/CVTF+4)
- GM/SATURN (DEX-CVT)
- MERCEDES BENZ (236.20)

NOT RECOMMENDED FOR HYBRID CVT UNITS (TOYOTA AND FORD)
NOT FOR USE IN CONVENTIONAL AUTOMATIC TRANSMISSIONS.

CODE	GRADE	PACKING	MATERIAL
LMOCVT-121-P	CVT	12x1L	PLASTIC
LMOCVT-45-P	CVT	4x5L	PLASTIC

GRADE	UNIT	CVT
Colour	-	Light Orange
Viscosity @ 100°C	cSt	6
Viscosity @ 40°C	cSt	27
Flash Point, COC	°C / °F	196 / 384.8
Pour Point	°C / °F	-48 / -54.4
Viscosity Index	None	179
Brookfield Viscosity @ -40°C	cPat	12900
Specific Gravity @ 15.6°C	-	0.8506



LAUNCH its performance>>

