



LAUNCHER DEXRON III / MERCON AUTOMATIC TRANSMISSION FLUID

LAUNCHER ATF Dexron III is an automatic transmission fluid formulated to meet the requirements of the General Motors Specifications GM 6297M for a Dexron III Fluid and Ford Mercon for Ford transmission. ATF Dexron III is a premium automatic transmission fluid specially formulated to meet the needs of today's more compact transmissions, running at higher operating temperatures and with electronic control. ATF Dexron III is recommended for use in automatic transmissions, where the manufacturer prescribes a GM Dexron IIE, Dexron III, or Ford Mercon fluid.



APPLICATIONS

LAUNCHER Dexron III / Mercon is a premium quality automatic transmission fluid recommended for pre 2006 GM and Ford vehicles as well as hydraulic and power steering systems. Not recommended when Ford Type F or Ford Mercon V/LV/SP Transmission fluid is required.

PERFORMANCE FEATURES AND BENEFITS

- Superior Protection: Through use of advanced additive chemistry ATF DX-3 fights the three major causes of transmission failure heat, deposits and wear.
- Enhanced viscosity control: Delivers improved performance and durability.
- Cold start properties: Low temperature viscosity results improved shift performance at low temperatures.
- Wear protection: Excellent wear protection enhances transmission life and shift consistency.

RECOMMENDATIONS / SPECIFICATIONS

MEETS OR EXCEEDS :
PRE-2006 GM and Ford vehicles.

TYPICAL TECHNICAL PROPERTIES

PRODUCT CODE	LMODEX3
ASTM D1500 Colour	Red
Density at 15.6°C, g/ml, ASTM D4052	0.846
Kinematic Viscosity at 40°C, mm ² /s, ASTM D445	36.3
Kinematic Viscosity at 100°C, mm ² /s, ASTM D445	7.4
Viscosity Index, ASTM D2270	176
Flash Point (COC), °C, ASTM D92	220
Pour Point, °C, ASTM D97	-51
Brookfield viscosity at -40°C, mPa.s, ASTM D2983	10040

Note: These characteristics are typical of current production. While future production will conform to LAUNCHER'S specification, variations in these characteristics may occur.



Packing : 1L | 4L | 5L | 208L/Drum

Version : LL/TDS/DEX3/V1/02-01-2023

Health and Safety: This lubricant, when used in accordance with our recommendations and for the application for which it is intended, does not constitute any special hazard. A safety data file conforming to the requirements of current EC legislation is available from your local trade consultant